

ARMY RESEARCH LABORATORY



The Refractive Index Structure Parameter/Atmospheric Optical Turbulence Model: CN2

by Arnold D. Tunick

ARL-TR-1615

April 1998

DTIC QUALITY INSPECTED 4

19980416 177

Approved for public release; distribution unlimited.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Adelphi, MD 20783-1197

ARL-TR-1615

April 1998

The Refractive Index Structure Parameter/Atmospheric Optical Turbulence Model: CN2

Arnold D. Tunick

Information Science and Technology Directorate

Abstract

The CN2 model is a semi-empirical algorithm that makes a quantitative assessment of atmospheric optical turbulence. The algorithm uses surface layer gradient assumptions applied to two levels of discrete vertical profile data to calculate the refractive index structure parameter. Model results can be obtained for unstable, stable, and near-neutral atmospheric conditions. The CN2 model has been benchmarked on data from the REBAL '92 field study. The model will shortly be added to the Electro-Optics Atmospheric Effects Library (EOSAEL). This report gives technical and user's guide information on the CN2 model.

Contents

1. Introduction	1
2. Mathematical Description of CN2 Model	3
3. Verification	9
4. CN2 Module User's Information	12
5. Input/Output Examples	13
5.1 <i>Calculation for Unstable Atmospheric Conditions</i>	13
5.2 <i>Calculation for Stable Atmospheric Conditions</i>	14
5.3 <i>Calculation for Near-Neutral Atmospheric Conditions</i>	15
6. Summary	16
References	17
Distribution	21
Report Documentation Page	27

Figures

1. Time series of scintillometer data compared to CN2 model output, determined from input data at 1 and 4 m above ground, 2 and 4 m above ground, and 4 and 8 m above ground	10
2. Time series of temperature data collected during REBAL '92 field study, 8–9 July 1992	11
3. Time series of calculated temperature gradients from data collected during REBAL '92 field study, 8–9 July 1992	11

Tables

1. List of symbols	4
2. CN2 model input cards and parameter range restrictions	12

1. Introduction

Atmospheric optical turbulence is a problem for most electro-optical (EO) systems. The image distortion it promotes can drastically reduce system and sensor performance. A means of assessing the levels of optical turbulence, relying on calculations that require a minimum of atmospheric data, could be an advantage to those in the field of EO system design and application. This report introduces the CN2 model, a semi-empirical algorithm developed by the Army Research Laboratory (ARL) for inclusion into the Electro-Optics Atmospheric Effects Library (EOSAEL), which addresses the atmospheric optical turbulence problem.

The propagation of a light beam through the atmosphere is affected by random fluctuations in the refractive index of air (Kunkel et al., 1981). These fluctuations or discontinuities cause *optical turbulence*—variations in the speed at which the wavefront propagates. The refractive index structure parameter (C_n^2) is a quantitative measure of optical turbulence.

The value of C_n^2 has been generally observed to range from about 10^{-12} to $10^{-16} \text{ m}^{-2/3}$. High values of C_n^2 , $10^{-12} \text{ m}^{-2/3}$ or greater, even over nominal distances, usually indicate turbulent atmospheres wherein considerable visual blurring or image distortion would be present (as if one were looking out over a hot paved road, over an airport runway, or, in an extreme case, through the exhaust behind a jet engine). At lower values of C_n^2 , 10^{-16} to $10^{-15} \text{ m}^{-2/3}$, atmospheric optical turbulence would generally be considered negligible. (However, there could be other image-degrading effects arising from other factors, such as precipitation, fog, or smoke.)

Many simulation models have been developed that address optical turbulence in the atmospheric surface layer (Kunkel et al, 1981; Andreas, 1988; Miller and Ricklin, 1990; Tunick and Rachele, 1991; Sadot and Kopeika, 1992; Tofsted, 1993; and Rachele and Tunick, 1994); these models vary both in mathematical complexity and in the amounts and types of inputs and computer capabilities required. The CN2 model reported on here is a refractive index structure parameter model that makes a quantitative assessment of atmospheric optical turbulence given two levels of wind, temperature, and humidity profile data as input. It contains a surface layer profile structure algorithm derived by Rachele et al (1991, 1995, 1996a) that makes estimates of C_n^2 obtainable for unstable, stable, and near-neutral atmospheric conditions. CN2 also computes the surface heat and moisture flux.

This report gives a mathematical outline of the CN2 model, provides some user's guide information (sect. 4) on the new module intended for the EOSAEL, and provides output examples (sect. 5).

EOSAEL 95 is available at no cost to U.S. Government agencies, specified Allied organizations, and their authorized contractors. U.S. Government agencies needing EOSAEL 95 should send a letter of request, signed by a branch chief or division director, to the Army Research Laboratory (ARL). Contractors should have their Government contract monitors send the

letter of request. Allied organizations must request EOSAEL 95 through their national representatives. The EOSAEL point of contact at ARL is Dr. Alan Wetmore:

ARMY RESEARCH LABORATORY
2800 POWDER MILL ROAD
ATTN: AMSRL-IS-EE (DR. A. WETMORE)
ADELPHI, MD 20783-1157

Phone: (301) 394-2499
DSN: 290-2499
Fax: (301) 394-4797
Email: awetmore@arl.mil

Letters of request should include intended uses and the type of nine-track tape necessary for computer execution: ASCII, UNIX, tar format in 1600 or 6250 bpi, or SUN cartridge (EOSAEL 95 cannot be supplied on media other than these). Documentation for modules is included.

2. Mathematical Description of CN2 Model

The proposal to include CN2 in the EOSAEL was drafted only recently. The model itself, however, is based on a combination of concepts and algorithms that had been developed and partially validated over a number of years, such as those documented in Rachele et al (1991, 1995, 1996ab), Tunick and Rachele (1991), Rachele and Tunick (1992, 1994), and Tunick et al (1994). The motivation for these studies was principally to develop and verify a set of equations for the atmospheric stability portion of the calculations needed to evaluate an expression for C_n^2 , such as the one given in Tatarski (1961), which can be written as

$$C_n^2(z) = b \frac{K_H}{\epsilon^{1/3}} \left(\frac{\partial n}{\partial z} \right)^2, \quad (1)$$

where b is equal to 3.2 and called the Obukhov-Corrsin constant, K_H is the turbulent exchange coefficient for heat diffusion, ϵ is the energy dissipation rate (Panofsky, 1968), and $\partial n/\partial z$ is the vertical gradient of the index of refraction, n . A list of symbols and constants is given in table 1.

For visible and IR wavelengths, the expression for $\partial n/\partial z$, as presented by Tunick and Rachele (1991), is based on work reported by Andreas (1988). Andreas's formulations, which are expressed in terms of gradients of temperature and *absolute* humidity, were modified to expressions in terms of gradients of potential temperature θ and *specific* humidity q , as required by Tatarski (1961). For the visible region and near-infrared wavelengths from 0.36 to 3 μm (as denoted by the subscript v), Andreas (1988) writes

$$n_v = 1 + \left(M_1(\lambda) \frac{P}{T} + 4.615 (M_2(\lambda) - M_1(\lambda)) Q \right) \times 10^{-6}, \quad (2)$$

where

$$M_1(\lambda) = 23.7134 + \frac{6839.397}{130 - \sigma^2} + \frac{45.473}{38.9 - \sigma^2}, \quad (3)$$

and

$$M_2(\lambda) = 64.8731 + 0.58058 \sigma^2 - 0.007115 \sigma^4 + 0.0008851 \sigma^6. \quad (4)$$

Transforming equation (2) in terms of potential temperature (θ) and specific humidity (q) yields

$$n_v = 1 + \left(M_1(\lambda) \frac{P}{\theta - \gamma_d(z - z_r)} + 1.60948 [M_2(\lambda) - M_1(\lambda)] \frac{Pq}{\theta - \gamma_d(z - z_r)} \right) \times 10^{-6}. \quad (5)$$

Table 1. List of symbols.

Symbol	Name or description	Value or equation	Literature reference
C_n^2	refractive index structure parameter	$C_n^2 = b \frac{K_H}{\varepsilon^{1/3}} \left(\frac{\partial n}{\partial z} \right)^2$	
b	Obukhov-Corrsin constant	3.2	Panofsky (1968), Wyngaard (1973), Andreas (1988), Hill (1989)
g	gravitational acceleration	9.8 m/s ²	—
k	von Karman's constant	0.4	Businger et al (1971)
K_H	turbulent exchange coefficient for heat	$K_H = u_* k z / \phi_H(\zeta)$	Businger et al (1971)
L	Obukhov scaling length	$L = u_*^2 \theta / k g \theta_*$	Obukhov (1946)
$M_1(\lambda)$	constant in eq (6) and (11)	—	—
$M_2(\lambda)$	constant in eq (6)	—	—
n_i	index of refraction (infrared)	—	Andreas (1988)
n_{iw}	refractivity due to water vapor	—	Hill and Lawrence (1986)
n_V	index of refraction (visible)	—	Andreas (1988)
n_{Vd}	contribution from dry air to instantaneous refractivity	—	Owens (1967)
P	atmospheric pressure in millibars	—	—
q	specific humidity (kg/kg)	—	—
Q	absolute humidity (kg/m ³)	—	—
T	air temperature (K)	—	—
V	wind velocity (m/s)	—	—
X	scaled wavelength	10 $\mu\text{m}/\lambda$	—
z	height (m) above ground	—	—
z_r	reference height above ground	2 m	—
θ_*	potential temperature scaling parameter	$\theta_* = \frac{k \Delta \theta}{\phi_H \Delta \ln z}$	Rachele et al (1995)

Table 1. List of symbols (cont'd).

Symbol	Name or description	Value or equation	Literature reference
θ_{v*}	potential temperature scaling parameter	$\theta_{v*} = \frac{k\Delta\theta_v}{\phi_H\Delta \ln z}$	Rachele et al (1995)
q_*	specific humidity scaling constant	$q_* = \frac{k\Delta q}{\phi_H\Delta \ln z}$	Rachele et al (1995)
u_*	friction velocity	$u_* = \frac{k\Delta V}{\phi_m\Delta \ln z}$	Rachele et al (1995)
z^*	logarithmic mean scaling height	$z^* = \frac{\Delta z}{\Delta \ln z}$	Rachele et al (1995)
α	scaled temperature	$T/273.15$	—
Δ	difference operator	(i.e., $\Delta\theta = \theta_2 - \theta_1$)	—
ε	energy dissipation rate	$\varepsilon = u_*^3 (\phi_m - \zeta)/kz$	Panofsky (1968)
λ_d	dry adiabatic lapse rate	$-0.00098 \text{ }^\circ\text{C/m}$	—
λ	wavelength (μm)	—	—
$\phi_H(\zeta)$	dimensionless temperature lapse rate	$\phi_H(\zeta) = (1 - 15\zeta)^{-1/2}$ for $\zeta < 0$ $\phi_H(\zeta) = 1 + 5\zeta$ for $\zeta > 0$	Dyer (1974), Hicks (1976) Webb (1970)
$\phi_m(\zeta)$	dimensionless wind shear	$\phi_m(\zeta) = (1 - 15\zeta)^{-1/4}$ for $\zeta < 0$ $\phi_m = \phi_H$ for $\zeta > 0$	Dyer (1974), Hicks (1976) Webb (1970)
ϕ_q	nondimensional specific humidity lapse	$\phi_q = \phi_H$	—
θ	potential temperature	$\theta \approx T + 0.0098 \times (z - z_r)$	Rachele and Tunick (1994)
θ_v	virtual potential temperature	$\theta_v = \theta(1 + 0.61q)$	Busch (1973)
σ	1/wavelength	λ^{-1}	—
ζ	scaling ratio	z/L	Monin and Obukhov (1954)
$\frac{\partial\theta}{\partial z}$	vertical gradient of potential temperature	$\frac{\partial\theta}{\partial z} = \frac{\theta_*}{kz} \phi_H$	Busch (1973)
$\frac{\partial\theta_v}{\partial z}$	vertical gradient of virtual potential temperature	$\frac{\partial\theta_v}{\partial z} = \frac{\theta_{v*}}{kz} \phi_H$	Busch (1973)

Table 1. List of symbols (cont'd).

Symbol	Name or description	Value or equation	Literature reference
$\frac{\partial q}{\partial z}$	vertical gradient of specific humidity	$\frac{\partial q}{\partial z} = \frac{q^*}{kz} \phi_H$	Busch (1973)
$\frac{\partial V}{\partial z}$	vertical gradient of wind velocity	$\frac{\partial V}{\partial z} = \frac{u_*}{kz} \phi_m$	Busch (1973)
[A], [B]	placement variables in eq (11)	—	—
$\partial n / \partial z$	vertical gradient of mean refractive index	—	Tunick and Rachele (1991)
$\frac{\partial n_i}{\partial z}$	vertical gradient of index of refraction (infrared)	—	Tunick and Rachele (1991)
$\frac{\partial n_v}{\partial z}$	vertical gradient of index of refraction (visible)	—	Tunick and Rachele (1991)

For steady-state, homogeneous conditions, equation (5) yields

$$\begin{aligned} \frac{\partial n_v}{\partial z} = & \left(-M_1(\lambda) \frac{P}{T^2} - 1.61 (M_2(\lambda) - M_1(\lambda)) \frac{Pq}{T^2} \right) \times 10^{-6} \frac{\partial \theta}{\partial z} \\ & + 1.61 (M_2(\lambda) - M_1(\lambda)) \frac{P}{T} \times 10^{-6} \frac{\partial q}{\partial z} . \end{aligned} \quad (6)$$

For IR wavelengths from 7.8 to 19 μm (as denoted by the subscript i) Andreas (1988) (who refers to Hill and Lawrence (1986) and Owens (1967)) writes

$$n_i = 1 + (n_{vd} + n_{iw}) \times 10^{-6} , \quad (7)$$

where in the range from -40.0 to $+40.0$ $^{\circ}\text{C}$,

$$n_{iw} = Q \left[\frac{957. - 928. \alpha^{0.4} (X - 1)}{1.03 \alpha^{0.17} - 19.8 X^2 + 8.2 X^4 - 1.7 X^8} + \frac{3.747 \times 10^6}{12,499. - X^2} \right] , \quad (8)$$

and

$$n_{vd} = M_1(\lambda) \frac{P}{T} - 4.615 M_1(\lambda) Q . \quad (9)$$

Substituting Q (kg/m^3) = $0.34875 Pq/T$ into equations (8) and (9), and taking the derivative of equation (7) in terms of θ and q gives

$$\frac{\partial n_i}{\partial z} = \left(-M_i(\lambda) \frac{P}{T^2} - 1.6095 M_i(\lambda) \frac{Pq}{T^2} + 0.34875 \frac{Pq}{T} [A] - 0.34875 [B] \frac{Pq}{T^2} \right) \times 10^{-6} \frac{\partial \theta}{\partial z} \\ + (0.34875 [B] - 1.6095 M_i(\lambda)) \frac{P}{T} \times 10^{-6} \frac{\partial q}{\partial z} , \quad (10)$$

where

$$[A] = \left(-\frac{1.359\alpha^{-0.6}(X-1)}{1.03\alpha^{0.17} - 19.8X^2 + 8.2X^4 - 1.7X^8} + \frac{0.5949\alpha^{0.43}(X-1)}{(1.03\alpha^{0.17} - 19.8X^2 + 8.2X^4 - 1.7X^8)^2} \right) \quad (11)$$

and

$$[B] = \left[\frac{957. - 928.\alpha^{0.4}(X-1)}{1.03\alpha^{0.17} - 19.8X^2 + 8.2X^4 - 1.7X^8} + \frac{3.747 \times 10^6}{12499. - X^2} \right] . \quad (12)$$

The surface layer algorithm called MARIAH (Rachele et al, 1991, 1995, 1996a,b) is used to obtain a noniterative solution for the temperature and moisture partial derivatives $\partial\theta/\partial z$ and $\partial q/\partial z$. The MARIAH algorithm is based on a series of concepts more commonly known as similarity theory (as defined by the earlier efforts discussed in Obukhov (1946), Monin and Obukhov (1954), Businger et al (1971), and Busch (1973)).

As similarity theory prescribes, the partial derivatives of wind speed, temperature, and moisture with respect to height can be written as

$$\frac{\partial V}{\partial z} = \frac{u_*}{kz} \phi_m , \quad \frac{\partial \theta}{\partial z} = \frac{\theta_*}{kz} \phi_H , \quad \frac{\partial q}{\partial z} = \frac{q_*}{kz} \phi_q , \quad (13)$$

where V is wind speed (m/s), u_* is the friction velocity (m/s), θ_* is the potential temperature scaling constant (K), q_* is the specific humidity scaling constant (g/g), z is height above ground, k is Karman's constant (0.4), and ϕ_m , ϕ_H , and ϕ_q are the dimensionless wind shear, dimensionless temperature lapse rate, and dimensionless humidity lapse rate, respectively. The MARIAH algorithm suggests that the partial differential equations in equation (13) can be re-expressed as

$$u_* = \frac{k\Delta V}{\phi_m \Delta \ln z} , \quad \theta_* = \frac{k\Delta \theta}{\phi_H \Delta \ln z} , \quad q_* = \frac{k\Delta q}{\phi_H \Delta \ln z} , \quad (14)$$

where the Δ operator refers to the difference in data taken from one tower level to another (i.e., $V_2 - V_1$). Here, the dimensionless term for humidity is assumed equal to the dimensionless temperature lapse (i.e., $\phi_q = \phi_H$), even though field observations have shown that atmospheric gradients of temperature do not always or universally behave similarly to those of moisture. The relationships in equation (14) can be handled in a straight-

forward manner, given expressions for the dimensionless shear and lapse rate terms. Following Dyer (1974) and Hicks (1976), I use

$$\phi_m = [1 - 15(z/L)]^{-1/4} \text{ and } \phi_H = [1 - 15(z/L)]^{-1/2} \quad (15)$$

for unstable atmospheric conditions, and from Webb (1970), I use

$$\phi_m = \phi_H = 1 + 5(z/L) , \quad (16)$$

for stable atmospheric conditions. Busch (1973) defines the Monin-Obukhov (M-O) scaling ratio as

$$\frac{z}{L} = k \frac{g}{\theta_v} \frac{\theta_{v*}}{u_*^2} z , \quad (17)$$

where $\theta_v = \theta(1 + 0.61q)$ is the virtual potential temperature, and $\theta_{v*} = \theta_* + 0.61\theta q_*$ is the virtual potential temperature scaling constant. (This equation for the M-O scaling ratio, which reflects atmospheric stability in terms of the scaling constants in eq (14), includes the effects of water (vapor) content by considering the dry or virtual atmosphere. The virtual temperature is the temperature that dry air must have to equal the density of moist air at the same pressure (Stull, 1988).) Therefore, from equations (14) and (17), the expression for the Obukhov length L used in equations (15) and (16) can be formulated as

$$L = \frac{1}{\Delta \ln z} \frac{\theta_v}{g} \frac{(\Delta V)^2 \phi_H}{[\Delta \theta + 0.61 \theta \Delta q] \phi_m^2} , \quad (18)$$

so that for unstable atmospheric conditions,

$$L = \frac{1}{\Delta \ln z} \frac{\theta_v}{g} \frac{(\Delta V)^2}{\Delta \theta + 0.61 \theta \Delta q} . \quad (19)$$

For stable atmospheric conditions, it can be expressed as

$$L \phi_m = \frac{1}{\Delta \ln z} \frac{\theta_v}{g} \frac{(\Delta V)^2}{\Delta \theta + 0.61 \theta \Delta q} . \quad (20)$$

Note that the gradients for each layer should be taken to mean those tangent to the indicated profiles at $z = z^*$, where $z^* = \Delta z / (\Delta \ln z)$, instead of $z^* = (z_1 \cdot z_2)^{1/2}$, the geometric mean, which is almost always assumed (Rachele and Tunick, 1991; Rachele et al, 1991). The relationships for profiles of C_n^2 , which are generally accepted for $z \leq |L|$, can be expressed as

$$C_n^2(z) = C_n^2(z^*) \cdot \left(\frac{z}{z^*}\right)^{-4/3} \text{ and } C_n^2 = C_n^2(z^*) \cdot \left(\frac{z}{z^*}\right)^{-2/3} , \quad (21)$$

for unstable and stable or near-neutral atmospheric conditions, respectively, where the $-4/3$ and $-2/3$ behavior had been indicated by experimental surface layer data (as discussed in somewhat more detail by Wyngaard, 1973, and Wyngaard and LeMone, 1980).

3. Verification

The CN2 model was benchmarked using the data collected during the field study entitled "Radiation Energy Balance Experiment for Imagery and EM Propagation" (REBAL '92). REBAL '92 (Tunick et al, 1994) was conducted during May and July 1992 at Bushland, TX (35°N latitude, 102°W longitude, 1170-m elevation above mean sea level) by the Army Research Laboratory and the Conservation and Production Research Laboratory (CPRL) of the USDA Agricultural Research Service (ARS). (The test site at ARS-CPRL in Bushland, TX, is approximately 16 km due west of Amarillo.) Diurnal measurements of sky and emitted radiation, soil heat flux, soil temperature and volumetric water content, evaporation, optical turbulence (from a scintillometer*), near- and far-field infrared imager data, and micrometeorological profile data were collected over wet and dry bare soil for clear and cloudy sky conditions.


The micrometeorological profiles of wind speed, temperature, and relative humidity were measured on an 8-m tower centered in the test area (at 0.5, 1., 2., 4., and 8. m above the surface). A 0.94- μ m scintillometer (Lockheed Engineering & Management IV-L) source module was mounted 2 m above ground on a tripod at the north end of the test area and was aligned and focused down-field (i.e., to the south) over a path of approximately 450 m.

Figure 1 shows time series from CN2 model results compared to time series of the observed data. Each plot reflects conditions during the same collection interval (i.e., 8 July 1992, 1230 local time (LT), to 9 July 1992, 2100 LT), except that the wind speed, temperature, and relative humidity input data (15-min averaged) are taken from different heights above ground (that is, 1 and 4 m, 2 and 4 m, and 4 and 8 m above ground, respectively).

Overall, the C_n^2 estimates appear to be in line with the observations. However, there are several instances when the CN2 model results are in extreme contrast to the scintillometer data. These occur numerically when the computed temperature gradients are very, very small: small enough to cause singularities in the model calculations. They occur physically during periods, however brief, of near-neutral or neutral atmospheric stability. Figure 2 is a time series of temperature data, measured at four heights above ground level. Segments of the data (indicated on the figure by arrows) illustrate where differences in temperature from one level to the next (i.e., the gradients) are slight and nearly impossible to distinguish. Apparently, the CN2 model's "local-gradient" approach tends to exaggerate the near-zero- and zero-gradient situations. Future studies using more complex sets of equations for the atmosphere may help to improve upon turbulence assessments at these times.

*Scintillometers are ground-based, remote-sensing instruments designed to measure optical turbulence intensity along a line-of-sight path established between a transmitter and a downrange receiver. Scintillometer operation is based on the principle that scintillations or light intensity variations occur as atmospheric density discontinuities create refraction effects in light propagating along a path (Clifford et al, 1974). The refractive index structure parameter C_n^2 is related to the intensity of these refraction effects.

Figure 1. Time series of scintillometer data compared to CN2 model output, determined from input data at (a) 1 and 4 m above ground, (b) 2 and 4 m above ground, and (c) 4 and 8 m above ground.



Finally, the time series analysis of temperature gradients shown in figure 3 implies that the most unstable gradients were described by data closer to the ground (resulting in higher estimates of optical turbulence during daytime hours). However, these data did not describe the greater stable gradients. An unexpected result from this study (as indicated in the figure by the solid squares) was that the greater stable gradients (and estimates of C_n^2) for much of the nighttime hours were described by data from 2 and 4 m.

Figure 2. Time series of temperature data collected during REBAL '92 field study, 8-9 July 1992.





Figure 3. Time series of calculated temperature gradients from data collected during REBAL '92 field study, 8-9 July 1992.



4. CN2 Module User's Information

CN2 is one of several new modules that ARL is developing for inclusion into the EOSAEL. This state-of-the-art computer library comprises fast-running, theoretical, semi-empirical, and empirical computer programs that mathematically describe aspects of electromagnetic propagation in battlefield environments. The modules are connected through an executive routine, but are often exercised individually (Wetmore et al, 1997).

There are four input file records (referred to as "input cards") that contain the wavelength and meteorological data for the CN2 model calculations. Two additional cards (not shown) control program execution. Table 2 gives descriptions of the CN2 model input cards, along with range restrictions recommended for the parameters that these cards control.

Table 2. CN2 model input cards and parameter range restrictions.

Card	Identifier	Variable	Description	Recommended range restrictions
1	WAVE	WV	Wavelength (μm)	Visible: $0.36 \mu\text{m} \leq \text{WV} \leq 3.0 \mu\text{m}$ IR: $7.8 \mu\text{m} \leq \text{WV} \leq 19.0 \mu\text{m}$
2	DATM	PR	Atmospheric pressure (mb) (at surface or either measurement height)	$700 \text{ mb} \leq \text{PR} \leq 1060 \text{ mb}$
3	LVL1	HGHT1	Height (m) above ground level, level 1 data	$\text{HGHT1} \leq \text{HGHT2} \leq 20 \text{ m}$ $\text{HGHT1} \neq \text{HGHT2}$ $\text{HGHT1} \geq 0.5 \text{ m}$ $\text{HGHT2} \geq 1.0 \text{ m}$ $0.5 \text{ m} \leq \text{HGHT2} - \text{HGHT1} \leq 18.0 \text{ m}$
		TEMP1	Temperature ($^{\circ}\text{C}$) at HGHT1	$\text{TEMP1} \neq \text{TEMP2}$ $-40.0 \text{ }^{\circ}\text{C} \leq (\text{TEMP1}, \text{TEMP2}) \leq +40.0 \text{ }^{\circ}\text{C}$
		WSPD1	Wind speed (m/s) at HGHT1	$\text{WSPD1} < \text{WSPD2}$ $0.0 \text{ m/s} \leq \text{WSPD1} \leq 18.0 \text{ m/s}$ $1.0 \text{ m/s} \leq \text{WSPD2} \leq 18.0 \text{ m/s}$
		RHUM1	Relative humidity (%) at HGHT1	$0\% \leq (\text{RHUM1}, \text{RHUM2}) \leq 100\%$
4	LVL2	HGHT2 TEMP2 WSPD2 RHUM2	(parallel to LVL1 variables above)	(see above)

5. Input/Output Examples

In this section, I present examples of the input cards and formatted output produced by the CN2 model for the three general categories of atmospheric conditions: unstable, stable, and near-neutral atmospheric conditions. The following is the input file required for the three examples:

```
DATM      891.6      "Example 1"
LVL1       1.0      33.44    5.39    30.2
LVL2       4.0      31.42    6.35    32.9
WAVE       .94
GO
DATM      893.5      "Example 2"
LVL1       1.0      18.73    2.77    64.0
LVL2       4.0      19.06    3.80    64.6
GO
DATM      892.8      "Example 3"
LVL1       1.0      16.25    2.88    74.04
LVL2       4.0      16.20    3.72    75.05
DONE
```

5.1 Calculation for Unstable Atmospheric Conditions

Example 1 takes meteorological data from the REBAL '92 field study for 9 July 1992 at 1330 LT. The input data are representative of typical mid-afternoon, clear sky, unstable atmospheric conditions. The surface heat and moisture flux calculations reflect intense gradients of surface layer temperature and specific humidity. The computed C_n^2 at 2 m is on the order of 10^{-12} .

WAVELENGTH	.94	MICRONS
ATMOSPHERIC PRESSURE	891.60	MB
LEVEL1 METEOROLOGY AT	1.00	METERS
AIR TEMPERATURE	33.44	C
WINDSPEED	5.39	M/S
RELATIVE HUMIDITY	30.20	%
LEVEL2 METEOROLOGY AT	4.00	METERS
AIR TEMPERATURE	31.42	C
WINDSPEED	6.35	M/S
RELATIVE HUMIDITY	32.90	%
SURFACE HEAT FLUX	468.01	W/M ²
SURFACE MOISTURE FLUX	46	W/M ²
"UNSTABLE ATMOSPHERE"		
TEMPERATURE GRADIENT	-.6635E+00	DEGK/M
MOISTURE GRADIENT	-.1188E-03	G/G/M

REFRACTIVE INDEX STRUCTURE PARAMETER = CN^2 $M^{(-2/3)}$					
Z=1	Z=2	Z=5	Z=10	Z=15	Z=20
3.843E-12	1.525E-12	4.495E-13	1.784E-13	1.039E-13	7.079E-14

5.2 Calculation for Stable Atmospheric Conditions

Example 2 takes meteorological data from the REBAL '92 field study for 9 July 1992 at 0200 LT. The input data are representative of typical night-time atmospheric conditions under mostly cloudless skies. The calculated heat flux reflects a slight surface inversion in temperature within this weakly stable layer. The computed C_n^2 at 2 m is on the order of 10^{-14} .

WAVELENGTH	.94	MICRONS			
ATMOSPHERIC PRESSURE	893.50	MB			
LEVEL1 METEOROLOGY AT	1.00	METERS			
AIR TEMPERATURE	18.73	C			
WINDSPEED	2.77	M/S			
RELATIVE HUMIDITY	64.00	%			
LEVEL2 METEOROLOGY AT	4.00	METERS			
AIR TEMPERATURE	19.06	C			
WINDSPEED	3.80	M/S			
RELATIVE HUMIDITY	64.60	%			
SURFACE HEAT FLUX	-20.07	W/M^2			
SURFACE MOISTURE FLUX	-42.07	W/M^2			
"STABLE ATMOSPHERE"					
TEMPERATURE GRADIENT	.1198E+00	DEGK/M			
MOISTURE GRADIENT	.1005E-03	G/G/M			
REFRACTIVE INDEX STRUCTURE PARAMETER = CN^2 M^(-2/3)					

Z=1	Z=2	Z=5	Z=10	Z=15	Z=20

3.619E-14	2.280E-14	1.238E-14	7.798E-15	5.951E-15	4.912E-15

5.3 Calculation for Near-Neutral Atmospheric Conditions

Example 3 takes meteorological data from the REBAL '92 field study for 9 July 1992 at 0630 LT. The input data are representative of typical atmospheric conditions that tend to occur daily within an hour after sunrise. During this interval of time, there is almost always at least one instance of a near-neutral lapse in temperature as the ground warms with increasing amounts of incident solar radiation that begins to break up the nighttime inversion. The calculated surface fluxes at this time are small. The computed C_n^2 at 2 m is on the order of 10^{-17} .

WAVELENGTH	.94	MICRONS			
ATMOSPHERIC PRESSURE	893.00	MB			
LEVEL1 METEOROLOGY AT	1.00	METERS			
AIR TEMPERATURE	16.25	C			
WINDSPEED	2.88	M/S			
RELATIVE HUMIDITY	74.04	%			
LEVEL2 METEOROLOGY AT	4.00	METERS			
AIR TEMPERATURE	16.20	C			
WINDSPEED	3.72	M/S			
RELATIVE HUMIDITY	75.05	%			
SURFACE HEAT FLUX	1.45	W/M^2			
SURFACE MOISTURE FLUX	-17.62	W/M^2			
"NEAR-NEUTRAL ATMOSPHERE"					
TEMPERATURE GRADIENT	-.6866E-02	DEGK/M			
MOISTURE GRADIENT	.3327E-04	G/G/M			
REFRACTIVE INDEX STRUCTURE PARAMETER = CN^2 M^(-2/3)					

Z=1	Z=2	Z=5	Z=10	Z=15	Z=20

5.856E-17	3.689E-17	2.003E-17	1.262E-17	9.628E-18	7.948E-18

6. Summary

The CN2 model will shortly be added to the Electro-Optics Atmospheric Effects Library (EOSAEL). By applying surface layer gradient assumptions for two levels of wind, temperature, and humidity profile data to the calculation of the refractive index structure parameter C_n^2 , the CN2 model makes a quantitative assessment of atmospheric optical turbulence. The model was benchmarked on REBAL '92 field study data. CN2 will be made available to U.S. Government agencies, specified allied organizations, and their authorized contractors through ARL's EOSAEL point of contact, Alan Wetmore.

References

- Andreas, E. L., 1988: "Estimating C_n^2 over Snow and Sea Ice from Meteorological Data," *J. Opt. Soc. Am.* **5** (4), 481–495.
- Busch, N. E., 1973: "On the Mechanics of Atmospheric Turbulence," *Workshop on Micrometeorology*, D. A. Haugen (ed.), American Meteorological Society, Boston, MA, pp 1–65.
- Businger, J. A., J. C. Wyngaard, Y. Izumi, and E. F. Bradley, 1971: "Flux-Profile Relationships in the Atmospheric Surface Layer," *J. Atmos. Sci.* **28**, 181–189.
- Clifford, S. F., G. R. Ochs, and R. S. Lawrence, 1974: "Saturation of Optical Scintillation by Strong Turbulence," *J. Opt. Soc. Am.* **64**, 148–154.
- Dyer, A. J., 1974: "A Review of Flux-Profile Relationships," *Bound.-Layer Meteorol.* **7**, 363–372.
- Hicks, B. B., 1976: "Wind Profile Relationships from the Wangara Experiment," *Q. J. R. Meteorol. Soc.* **102**, 535–551.
- Hill, R. J., 1989: "Implications of Monin-Obukhov Similarity Theory for Scalar Quantities," *J. Atmos. Sci.* **46**, 2236–2244.
- Hill, R. J., and R. S. Lawrence, 1986: "Refractive Index of Water Vapor in Infrared Windows," *Infrared Phys.* **26**, 371–376.
- Kunkel, K. E., D. L. Walters, and G. A. Ely, 1981: "Behavior of the Temperature Structure Parameter in a Desert Basin," *J. Appl. Meteorol.* **20**, 130–136.
- Miller, W. B., and J. C. Ricklin, 1990: *A Module for Imaging Through Optical Turbulence: IMTURB*, Atmospheric Sciences Laboratory, ASL-TR-0221-27 (available from Army Research Laboratory).
- Monin, A. S., and A. M. Obukhov, 1954: "Basic Regularity in Turbulent Mixing in the Surface Layer of the Atmosphere," *Trans. Geophys. Inst. (Trudy) Acad. Sci. USSR* **24**, 163–187.
- Obukhov, A. M., 1946: "Turbulence in an Atmosphere of Non-Homogeneous Temperature," *Trans. Inst. Theor. Geophys. USSR* **1**, 95–115.
- Owens, J. C., 1967: "Optical Refractive Index of Air; Dependence on Pressure Temperature and Composition," *Appl. Opt.* **6**, 51–59.
- Panofsky, H. A., 1968: "The Structure Constant for the Index of Refraction in Relation to the Gradient of the Index of Refraction in the Surface Layer," *J. Geophys. Res.* **73**, 6047–6049.
- Rachele, H., and A. Tunick, 1991: *On the Subject of Geometric Spacing of Meteorological Sensors*, Atmospheric Sciences Laboratory, ASL-TMR-0011 (available from Army Research Laboratory).

- Rachele, H., A. Tunick, and F. V. Hansen, 1991: *A Method for Estimating Similarity Scaling and Obukhov Lengths from Discrete Vertical Profile Data*, Atmospheric Sciences Laboratory, ASL-TR-0303 (available from Army Research Laboratory).
- Rachele, H., and A. Tunick, 1992: *Sensitivity of C_n^2 to Random Variations of Windspeed, Sensible Heat Flux, and Latent Heat Flux*, Atmospheric Sciences Laboratory, ASL-TR-0308 (available from Army Research Laboratory).
- Rachele, H., and A. Tunick, 1994: "Energy Balance Model for Imagery and Electromagnetic Propagation," *J. Appl. Meteorol.* **33**, 964–976.
- Rachele, H., A. Tunick, and F. V. Hansen, 1995: "MARIAH—A Similarity Based Method for Determining Wind, Temperature, and Humidity Profile Structure in the Atmospheric Surface Layer," *J. Appl. Meteorol.* **34**, 1000–1005.
- Rachele, H., A. Tunick, and F. V. Hansen, 1996a: "Reply," *J. Appl. Meteorol.* **35** (4), 613–614. (Reply to Arya, S. P., 1996: "Comments on 'MARIAH—A Similarity Based Method for Determining Wind, Temperature, and Humidity Profile Structure in the Atmospheric Surface Layer,'" *J. Appl. Meteorol.* **35** (4), 610–612.)
- Rachele, H., A. Tunick, L. Kordova, and Y. Mahrer, 1996b: "A Radiation and Energy Balance Model for the Microscale-Surface Layer Environment," *Proc. 22nd Conf. Agri. Forest Meteorol.*, 28 January–2 February, Atlanta, American Meteorological Society, Boston.
- Sadot, D., and N. S. Kopeika, 1992: "Forecasting Optical Turbulence Strength on the Basis of Macroscale Meteorology and Aerosols: Model and Validation," *Opt. Eng.* **31** (2), 200–212.
- Stull, R. B., 1988: *An Introduction to Boundary Layer Meteorology*, Kluwer Academic Publishers.
- Tatarski, V. I., 1961: *Wave Propagation in a Turbulent Medium*, McGraw-Hill.
- Tofsted, D. H., 1993: *A Surface Energy Budget Model Modifying Heat Flow by Foliage Effects*, Army Research Laboratory, ARL-TR-60.
- Tunick, A., 1995: "ARL Professional Exchange Program (APEX) to Israel," *Proc. Battlefield Atmospherics Conference*, 28–30 November, White Sands Missile Range, NM (available from Army Research Laboratory).
- Tunick, A., and H. Rachele, 1991: "Estimating the Effects of Temperature and Moisture on C_n^2 in the Damp Unstable Boundary Layer for Visible, Infrared, Radio, and Millimeter Wavelengths," *Proc. Battlefield Atmospherics Conference*, 3–6 December, Fort Bliss, TX (available from Army Research Laboratory).
- Tunick, A., H. Rachele, F. V. Hansen, T. A. Howell, J. L. Steiner, A. D. Schneider, and S. R. Evett, 1994: "REBAL '92—A Cooperative Radiation and Energy Balance Field Study for Imagery and EM Propagation," *Bull. Am. Meteorol. Soc.* **75**, 421–430.

Webb, W. K., 1970: "Profile Relationships: The Log-Linear Range, and Extension to Strong Stability," *Q. J. R. Meteorol. Soc.* **96**, 67–90.

Wetmore, A., P. Gillespie, A. McCann, and J. Schroeder, 1997: "EOSAEL—Current Work and Future Directions," *Proc. Battlespace Atmospherics Conference*, 2–4 December, San Diego, CA.

Wyngaard, J. C., 1973: "On Surface-Layer Turbulence," *Workshop on Micrometeorology*, D. A. Haugen (ed.), American Meteorological Society, Boston, MA, pp 101–149.

Wyngaard, J. C., and M. A. LeMone, 1980: "Behavior of the Refractive Index Structure Parameter in the Entraining Convective Boundary Layer," *J. Atmos. Sci.* **37** (3), 1573–1585.

Distribution

Admnstr
Defns Techl Info Ctr
Attn DTIC-OCP
8725 John J Kingman Rd Ste 0944
FT Belvoir VA 22060-6218

Mil Asst for Env Sci
Ofc of the Undersec of Defns for Rsrch &
Engrg R&AT ELS
Pentagon Rm 3D129
Washington DC 20301-3080

Ofc of the Dir Rsrch and Engrg
Attn R Menz
Pentagon Rm 3E1089
Washington DC 20301-3080

Ofc of the Secy of Defns
Attn ODDRE (R&AT) G Singley
Attn ODDRE (R&AT) S Gontarek
The Pentagon
Washington DC 20301-3080

OSD
Attn OUSD(A&T)/ODDDR&E(R) R Tru
Washington DC 20301-7100

ARL Chemical Biology Nuc Effects Div
Attn AMSRL-SL-CO
Aberdeen Proving Ground MD 21005-5423

Army Communications Elec Ctr for EW RSTA
Attn AMSEL-EW-D
FT Monmouth NJ 07703-5303

Army Corps of Engrs Engr Topographics Lab
Attn ETL-GS-LB
FT Belvoir VA 22060

Army Dugway Proving Ground
Attn STEDP 3
Attn STEDP-MT-DA-L-3
Attn STEDP-MT-M Biltoft
Attn STEDP-MT-M Bowers
Dugway UT 84022-5000

Army Field Artillery School
Attn ATSF-TSM-TA
FT Sill OK 73503-5000

Army Foreign Sci Tech Ctr
Attn CM
220 7th Stret NE
Charlottesville VA 22901-5396

Army Infantry
Attn ATSH-CD-CS-OR E Dutoit
FT Benning GA 30905-5090

Army Materiel Sys Analysis Activity
Attn AMXSU-AT Campbell
Attn AMXSU-CS Bradley
Aberdeen Proving Ground MD 21005-5071

Army Missile Cmnd
Attn AMSMI-RD-AC-AD Peterson
Redstone Arsenal AL 35898-5242

Army Missile Cmnd
Attn AMSMI-RD-DE-SE G Lill Jr
Redstone Arsenal AL 35898-5245

Army Missile Cmnd
Attn AMSMI-RD-AS-SS B Williams
Attn AMSMI-RD-AS-SS H F Anderson
Redstone Arsenal AL 35898-5253

Army Rsrch Ofc
Attn AMXRO-GS Bach
PO Box 12211
Research Triangle Park NC 27709

Army Strat Defns Cmnd
Attn CSSD-SL-L Lilly
PO Box 1500
Huntsville AL 35807-3801

Army TACOM-ARDEC
Attn AMSTA-AR-WEL-TL
Bldg 59 Phillips Rd
Picatinny Arsenal NJ 07806-5000

CECOM
Attn PM GPS COL S Young
FT Monmouth NJ 07703

CECOM RDEC Elect System Div Dir
Attn J Niemela
FT Monmouth NJ 07703

Distribution (cont'd)

CECOM
Sp & Terrestrial Commctn Div
Attn AMSEL-RD-ST-MC-M H Soicher
FT Monmouth NJ 07703-5203

Dpty Assist Secy for Rsrch & Techl
Attn SARD-TT F Milton Rm 3E479
The Pentagon
Washington DC 20301-0103

Hdqtrs Dept of the Army
Attn DAMO-FDT D Schmidt
400 Army Pentagon Rm 3C514
Washington DC 20301-0460

Hdqtrs Dept of the Army
Attn DAMI-POI
Washington DC 20301-1067

Kwajalein Missile Range
Attn Meteorologist in Charge
PO Box 57
APO San Francisco CA 96555

Natl Security Agency
Attn W21 Longbothum
9800 Savage Rd
FT George G Meade MD 20755-6000

Pac Mis Test Ctr Geophysics Div
Attn Code 3250 Battalino
Point Mugu CA 93042-5000

Science & Technology
101 Research Dr
Hampton VA 23666-1340

US Army Aviation Ctr
Attn ATZQ-D-MA Heath
FT Rucker AL 36362

US Army CECRL
Attn CECRL-RG Boyne
Hanover NH 03755-1290

US Army Chem School
Attn ATZN-CM-CC Barnes
FT McClellan AL 36205-5020

US Army Combined Arms Combat
Attn ATZL-CAW
FT Leavenworth KS 66027-5300

US Army Field Artillery Schl
Attn ATSF-F-FD Gullion
Attn ATSF-TSM-TA Taylor
FT Sill OK 73503-5600

US Army Intel Ctr and FT Huachuca
Attn ATSI-CDC-C Colanto
FT Huachuca AZ 85613-7000

US Army Materiel Sys Analysis Activity
Attn AMXSU-CR Marchetti
Aberdeen Proving Ground MD 21005-5071

US Army Matl Cmnd
Dpty CG for RDE Hdqtrs
Attn AMCRD BG Beauchamp
5001 Eisenhower Ave
Alexandria VA 22333-0001

US Army Matl Cmnd
Prin Dpty for Acquisition Hdqtrs
Attn AMCDCG-A D Adams
5001 Eisenhower Ave
Alexandria VA 22333-0001

US Army Matl Cmnd
Prin Dpty for Techlgy Hdqtrs
Attn AMCDCG-T M Fisette
5001 Eisenhower Ave
Alexandria VA 22333-0001

US Army Mis Cmnd (USAMICOM)
Attn AMSMI-RD-CS-R Documents
Redstone Arsenal AL 35898-5400

US Army Nuclear & Chem Agency
Attn MONA-ZB
Bldg 2073
Springfield VA 22150-3198

US Army OEC
Attn CSTE-EFS
Park Center IV 4501 Ford Ave
Alexandria VA 22302-1458

US Army Spc Technology Rsrch Ofc
Attn Brathwaite
5321 Riggs Rd
Gaithersburg MD 20882

Distribution (cont'd)

US Army Topo Engrg Ctr
Attn CETEC-ZC
FT Belvoir VA 22060-5546

US Army TRADOC Anlys Cmnd—WSMR
Attn ATRC-WSS-R
White Sands Missile Range NM 88002

US Army White Sands Missile Range
Attn STEWS-IM-IT Techl Lib Br
White Sands Missile Range NM 88002-5501

US Military Academy
Dept of Mathematical Sci
Attn MAJ D Engen
West Point NY 10996

USAASA
Attn MOAS-AI W Parron
9325 Gunston Rd Ste N319
FT Belvoir VA 22060-5582

USACRREL
Attn CEREL-GP R Detsch
72 Lyme Rd
Hanover NH 03755-1290

USATRADOC
Attn ATCD-FA
FT Monroe VA 23651-5170

Nav Air War Cen Wpn Div
Attn CMD 420000D C0245 A Shlanta
1 Admin Cir
China Lake CA 93555-6001

Nav Ocean Sys Ctr
Attn Code 54 Richter
San Diego CA 92152-5000

Nav Rsrch Lab
Attn Code 4110 Ruhnke
Washington DC 20375-5000

Nav Surface Warfare Ctr
Attn Code B07 J Pennella
17320 Dahlgren Rd Bldg 1470 Rm 1101
Dahlgren VA 22448-5100

Naval Surface Weapons Ctr
Attn Code G63
Dahlgren VA 22448-5000

Air Weather Service
Attn TechL Lib FL4414 3
Scott AFB IL 62225-5458

GPS Joint Prog Ofc Dir
Attn COL J Clay
2435 Vela Way Ste 1613
Los Angeles AFB CA 90245-5500

Hdqtrs AWS DOO 1
Scott AFB IL 62225-5008

Phillips Lab Atmos Sci Div
Geophysics Directorate
Attn McClatchey
Hanscom AFB MA 01731-5000

Phillips Lab Atmospheric Sci Div
Geophysics Dirctr
Kirtland AFB NM 87118-6008

Phillips Laboratory
Attn PL/LYP 3
Attn PL/LYP Chisholm
Attn PL/WE
Kirtland AFB NM 87118-6008

TAC/DOWP
Langley AFB VA 23665-5524

USAF Rome Lab Tech
Attn Corridor W Ste 262 RL SUL
26 Electr Pkwy Bldg 106
Griffiss AFB NY 13441-4514

USAFETAC DNE
Attn Glauber
Scott AFB IL 62225-5008

DARPA
Attn B Kaspar
Attn L Stotts
3701 N Fairfax Dr
Arlington VA 22203-1714

Nasa Marshal Space Flt Ctr
Atmospheric Sciences Div
Attn E501 Fichtl
Huntsville AL 35802

Distribution (cont'd)

Nasa Spct Flt Ctr Atmospheric
Sciences Div
Attn Code ED 41 1
Attn Code ED-41
Huntsville AL 35812

ARL Electromag Group
Attn Campus Mail Code F0250 A Tucker
University of Texas
Austin TX 78712

Colorado State Univ
Dept of Atmospheric Sci
Attn R A Pielke
FT Collins CO 80523

Cornell Univ School of Civil & Env
Attn W H Brutsaert
Hollister Hall
Ithica NY 14853-3501

Florida State Univ
Dept of Meteorology
Attn E A Smith
Tallahassee FL 32306

Iowa State Univ
Attn E S Takle
Attn R Arritt
312 Curtiss Hall
Ames IA 50011

Iowa State Univ
Attn M Segal
Attn S E Taylor
2104 Agronomy Hall
Ames IA 50011-1010

Michigan State Univ
Dept of Crop & Soil Sci
Attn J Ritchie
8570 Plant & Soil Sciences Bldg
East Lansing MI 48824-1325

Penn State Univ Dept of Meteorology
Attn D Thompson
503 Walker Bldg
University Park PA 16802

Rutgers Univ-Cook
Campus Envir & Natl Resources Bldg
Attn R Avissar
New Brunswick NJ 08903

Univ of Alabama at Huntsville Rsrch Instit
Attn R T McNider
Huntsville AL 35899

Univ of California at Davis
Dept of Air, Land, & Water Resources
Attn R H Shaw
Davis CA 95616

Univ of Connecticut
Dept of Renewable Natural Resources
Attn D R Miller
1376 Storrs Rd
Storrs CT 06269-4087

Univ of Nebraska
Dept of Agrcltl Meteorology
Attn S B Verma
Lincoln NE 68583-0728

University of Kansas
Dept of Physics & Astronomy
Attn J R Eagleman
Lawrence KS 66045

Washington State Univ
Dept of Agronomy & Soils
Attn G S Campbell
Pullman WA 99163

Agrclt Rsrch Svc Conserve & Prodn Rsrch Lab
Attn A D Schneider
Attn S R Evett
Attn T A HowellPO Drawer 10
Bushland TX 79012

Dean RMD
Attn Gomez
Washington DC 20314

Dept of Commerce Ctr
Mountain Administration
Attn Spprt Ctr Library R51
325 S Broadway
Boulder CO 80303

Distribution (cont'd)

Natl Ctr for Atmospheric Research
Attn NCAR Library Serials
Attn T W Horst
Attn S P Oncley
PO Box 3000
Boulder CO 80307-3000

NCSU
Attn J Davis
PO Box 8208
Raleigh NC 27650-8208

NTIA ITS S3
Attn H J Liebe
325 S Broadway
Boulder CO 80303

Pacific Missile Test Ctr Geophysics Div
Attn Code 3250
Point Mugu CA 93042-5000

Raytheon Company Equip div
Attn Sonnenschein
528 Boston Post Rd MS 1K9
Sudbury MA 01776

Sigma Rsrch Corp
Attn S R Hanna
544 Hill Rd
Boxborough MA 01719

USDA Agrcltl Rsrch Svc
Attn W P Kustas
BARCOWEST Bldg 265
Beltsville MD 20705

USDA Agrcltl Rsrch Svc
Attn R D Jackson
Attn S B Idso
4331 E Broadway Rd
Phoenix AZ 85040

USDA Forest Svc Rocky Mtn
Frst & Range Exprmnt Sta
Attn K F Zeller
240 W Prospect Stret
FT Collins CO 80526

US Army Rsrch Lab
Attn DRXRO-GS W Bach
PO Box 12211
Research Triangle Park NC 27009

US Army Rsrch Lab
Attn AMSRL-IS-EA J Harris
Attn AMSRL-IS-EW D Hoock
Battlefield Envir Dir
White Sands Missile Range NM 88002-5001

US Army Rsrch Lab
Attn AMSRL-CI-LL Techl Lib (3 copies)
Attn AMSRL-CS-AL-TA Mail & Records
Mgmt
Attn AMSRL-CS-AL-TP Techl Pub (3 copies)
Attn AMSRL-IS J D Gantt
Attn AMSRL-IS-E Brown
Attn AMSRL-IS-EE A D Tunick (15 copies)
Attn AMSRL-IS-EE D Garvey
Attn AMSRL-IS-EE R Meyers
Attn AMSRL-SE-EE Z G Sztankay
Adelphi MD 20783-1197

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE April 1998		3. REPORT TYPE AND DATES COVERED Final, from January to December 1997
4. TITLE AND SUBTITLE The Refractive Index Structure Parameter/Atmospheric Optical Turbulence Model: CN2			5. FUNDING NUMBERS DA PR: B53A PE: 61102A	
6. AUTHOR(S) Arnold D. Tunick				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory Attn: AMSRL-IS-EE (atunick@arl.mil) 2800 Powder Mill Road Adelphi, MD 20783-1197			8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-1615	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory 2800 Powder Mill Road Adelphi, MD 20783-1197			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES AMS code: 6110253A11 ARL PR: 7FEJ70				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The CN2 model is a semi-empirical algorithm that makes a quantitative assessment of atmospheric optical turbulence. The algorithm uses surface layer gradient assumptions applied to two levels of discrete vertical profile data to calculate the refractive index structure parameter. Model results can be obtained for unstable, stable, and near-neutral atmospheric conditions. The CN2 model has been benchmarked on data from the REBAL '92 field study. The model will shortly be added to the Electro-Optics Atmospheric Effects Library (EOSAEL). This report gives technical and user's guide information on the CN2 model.				
14. SUBJECT TERMS Micrometeorology, similarity theory			15. NUMBER OF PAGES 31	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	